

KemiLumin Sirius

SUBSTRATES

HRP Chemiluminescence Substrate

Cat. No. 5410

Lot No.: <u>xxxxxxxxx</u>

Date of manufacture: <u>mm-yyyy</u>

Expiry date: <u>mm-yyyy</u> (When stored at 2-8 °C in an unopened bottle)

Component A: The component contains luminol. Component B: The component contains peroxide.

Analysis: The substrate is analyzed for consistent activity, background, appearance, and pH.

Only the procedure for activity and background is described in the CoA.

Background: A working solution consisting of equal volumes of Component A & B is added to wells of a black microtiter plate and the chemiluminescence is read at 1

s/well with a chemiluminescence reader.

Activity: 100 pg HRP per well in solution are pipetted into wells of a black microtiter plate. A working solution consisting of equal volumes of Component A & B is added to each well and incubated for 10 minutes. The chemiluminescence is read at 1 s/well

with a chemiluminescence reader.

Specifications: Activity: $10.0 \cdot 10^6 - 14.0 \cdot 10^6 \text{ RLU}$

Background: < 100 RLU

Appearance: Component A: Clear solution with no distinct color

Component B: Clear solution with no distinct color Working solution: Clear solution with no distinct color

pH: Component A: 9.40 – 9.60

Component B: 4.85 – 5.05 Working solution: 8.70 – 8.90

Results: Activity: <u>Passed</u>

Background: Passed

Appearance: Component A: Passed

Component B: <u>Passed</u> Working solution: <u>Passed</u>

pH: Component A: Passed

Component B: <u>Passed</u> Working solution: <u>Passed</u>

Storage: Short-term storage: Ambient; component A must be protected from light.

Long-term storage: 2-8 °C; component A must be protected from light.

Performed by: Date: <u>dd-MMM-yyyy</u> Signature: <u>XX</u>

Approved by: Date: <u>dd-MMM-yyyy</u> Signature: <u>XX</u>

Our Immunoassay Solutions are developed in order to create a healthy and safe work environment and preserving natural resources, while helping our customers fulfill significant regulatory requirements. **We call it ECO-TEK!**

